Product Name: OPTILON, BLACK

Product Code: 857

Date issued: 2/28/2018

SECTION 1: IDENTIFICATION

Product Name OPTILON, BLACK

Product Code # 857

Identified Uses Protective Coating

Manufacturer: Kelley Technical Coatings

1445 South 15th Street P.O. Box 3726

Louisville, Kentucky 40201-3726

Emergency Contact Number: Day: 502-636-2561 Night: 800-424-9300

Information Telephone Number: 502-636-2561

SECTION 2: HAZARDS IDENTIFICATION

GHS Classification

Flammable Liquid 3 Aspiration Hazard 1 Skin Irritant 2

Eye Damage/Irritation 2A Acute Toxicity - Inhalation 4

Carcinogenicity 2

Specific Target Organ Toxicity (Single Exposure) 3

GHS Label Elements

Hazard Symbols



Signal Word Danger

Hazard Statements

H226 Flammable liquid and vapor

H304 May be fatal if swallowed and enters airways

H315 Causes skin irritation

H319 Causes serious eye irritation

H332 Harmful if inhaled

H351 Suspected of causing cancer

H336 May cause drowsiness or dizziness

Precautionary statements

Prevention

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. No Smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/fume/gas/mist/vapor/spray.

P271 Use only outdoors or in well-ventilated area.

P280 Wear PPE to protect skin/eyes.

P281 Use personal protective equipment as required.

Response

P312 Call a poison center or doctor if you feel unwell.

P363 Wash contaminated clothing and wash before reuse.

P301 + P310 If swallowed: Immediately call a poison center or doctor.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

 $P304 + P340 \ IF \ INHALED: \ Remove \ victim \ to \ fresh \ air \ and \ keep \ at \ rest \ in \ a \ position \ comfortable \ for \ breathing.$

P308 + P313 IF exposed or concerned: Get medical advice/attention.

 $P332 + P313 \; If \; skin \; irritation \; occurs: \; Get \; medical \; advice/attention.$

P337 + P313 If eye irritation persists: Get medical advice/attention.

Product Name: OPTILON, BLACK

Product Code: 857 Date issued: 2/28/2018

P370 + P378 In case of fire: Use ABC Dry Chemical for extinction.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rınsıng.

Storage/ Disposal

P405 Store locked up.

P501 Dispose of contents/container in accordance with federal, state, provincial, and local regulations.

P403 + P233 Store in well ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

OSHA Regulatory Status: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR1910.1200)

SECTION 3: COMPOSITION INFORMATION

Chemical Designation	CAS No.	% by Weight
nepheline syenite	37244-96-5	30 - 40%
4-chlorobenotrifluoride	98-56-6	20 - 30%
light aromatic naphtha	64742-95-6	10 - 20%
1,2,4 trimethylbenzene	95-63-6	5 - 10%
carbon black	1333-86-4	1 - 5%
cumene	98-82-8	0.1 - 1%
ethylbenzene	100-41-4	0.1 - 1%

SECTION 4: FIRST AID MEASURES

General Advice Show this safety data sheet to the doctor in attendance

Eyes: Flush with plenty of cool water for at least 15 minutes, holding eyelids apart for thorough irrigation. If irritation persists, get immediate

medical attention.

Skin: Wash affected area thoroughly with soap and water. If skin irritation persists, get immediate medical attention.

Inhalation: Move to fresh air. Restore breathing. If breathing is difficult, get immediate medical attention.

Ingestion: Do not induce vomiting – seek immediate medical attention.

Notes to Physician Treat symptomatically

SECTION 5: FIRE FIGHTING MEASURES

Extinguishing Media: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Specific Hazards arising from the Chemical

Closed containers may rupture if exposed to fire or extreme heat.

Special protective

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective

Equipment: gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protective equipment. Remove all sources of ignition.

Environmental Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from Precautions entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages

cannot be contained.

Methods for Clean-up Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface

thoroughly.

Other Information None known

SECTION 7: HANDLING & STORAGE

Handling: Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Avoid breathing

vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

Storage: Keep container tightly closed. Keep out of the reach of children.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

HMIS is a Health, Flammability and Reactivity rating: 2*21

HMIS CODE: 4 – SEVERE HAZARD, 3 – SERIOUS HAZARD, 2 – MODERATE HAZARD, 1 – SLIGHT HAZARD, 0 – MINIMAL HAZARD,

* - Chronic Hazard

Product Name: OPTILON, BLACK

Product Code: 857

Date issued: 2/28/2018

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual conditions of use

Exposure Limits

OSHA PEL ACGIH TLV **Hazardous Components** nepheline syenite 5 ppm (R) NF. 4-chlorobenotrifluoride NE NE light aromatic naphtha NE NE 1,2,4 trimethylbenzene 25 ppm 25 ppm carbon black 3.5 mg/m3 3 mg/m3 (I) cumene 50 ppm 50 ppm ethylbenzene 20 ppm 20 ppm

 $NE = None \ established \ NA = Not \ available \ (C) = Ceiling \ limit \ (I) = Inhalable \ fraction \ (IFV) = Inhalable \ fraction \ and \ vapor \ STEL = Short \ term \ exposure \ limit \ (R) = Respirable \ fraction$

Engineering Measures Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eyes/Face: Safety goggles or full face shield
Skin: Protective gloves and impervious clothing.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment.

Hygiene Practices: Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after

handling.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: liquid Not determined Little or no odor Odor threshold: Odor: VOC lb/gal 2.16 VOC (g/L) 259.00 VOC (lb/gal) less exempt 2.78 VOC (g/L) less exempt 333.77 Relative Density (LB/GAL): 11.10 Specific Gravity (g/L): 1.33 Flash Point (F): 110

Flammability: Not applicable Upper/lower flammability limits: Not applicable Auto-ignition temperature: Not applicable Decomposition temperature: Not determined

Evaporation rate : Not available

Vapor Pressure (mmHg): Not available Vapor Density: Not available 212 Boiling Point Range (F): Initial Boiling Point (F): Not available Freezing Point (F): 32 Melting Point (F): Not determined pН Not available Viscosity Not available

Solubility (ies): Not determined
Partition coefficient: n- Not determined

octanol/water

SECTION 10: STABILITY AND REACTIVITY

Chemical Stability: Stable under normal conditions.
Conditions to Avoid: Prevent from freezing

Conditions to Avoid: Prevent from freezing

Materials to Avoid:
Hazardous Decomposition Products:
Possibility of Hazardous Reactions:

No materials to be especially mentioned.
None under normal use.
None under normal conditions of use.

SECTION 11: TOXICOLOGICAL INFORMATION

Acute Toxicity			
Component	LD50 Oral mg/kg (Rat)	LD50 Dermal mg/kg (Rabbit)	LC50 Inhalation mg/L (Rat, 4 hr.)
		(Napolt)	
nepheline syenite	NA	NA	NA
4-chlorobenotrifluoride	NA	NA	NA
light aromatic naphtha	8,400	NA	NA
1,2,4 trimethylbenzene	5,000	18,000	NA
carbon black	15 400	3 000	NA

NA

5,000

NA

55,000

ethylbenzene Chronic Toxicity

cumene

The information below indicates whether each agency has listed any ingredient as a carcinogen:

NA

3,500

Component IARC NTP OSHA

Product Name: OPTILON, BLACK

Product Code: 857 Date issued: 2/28/2018

carbon black	2B – Possible Human Carcinogen	Not listed	Listed
cumene	2B – Possible Human Carcinogen	Not listed	Listed
ethylbenzene	2B – Possible Human Carcinogen	Not listed	Listed

Per IARC Summary of Data Reported, Subsection 5.1: No significant exposure to carbon black is thought to occur during the use of products in which carbon black is bound to other materials, such as rubber, printing ink or paint.

SECTION 12: ECOLOGICAL INFORMATION

No ecological information available

SECTION 13: DISPOSAL CONSIDERATION

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, Waste Disposal Method

consult your sanitation department or state-designated environmental protection agency for more disposal

options.

SECTION 14: TRANSPORT INFORMATION

Contact the manufacturer for shipping information.

SECTION 15: REGULATORY INFORMATION

US TSCA: Yes - All components are listed or exempt

Federal Regulations

SARA 311/312 hazardous categorization

Acute Health Hazard YES Chronic Health Hazard YES Fire Hazard NO Sudden Release of Pressure NO Hazard

Reactive Hazard NO

SARA 313

Section 313 OF Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). If listed below, this product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical Designation Cas No. Weight % 1,2,4 trimethylbenzene 95-63-6 5 - 10%

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPS)

Weight % **Chemical Designation** Cas No. cumene 98-82-8 0.21 100-41-4 ethylbenzene 0.10

Any Target HAP listed in this section is not an OSHA Carcinogen unless listed as such in Section 11 under Chronic Toxicity.

State Regulations

California Proposition 65

This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm.

SECTION 16: OTHER INFORMATION

Date issued: 2/28/2018 VER 04

The above Information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith. No warranty is implied with respect to the quality or the specification of the product and the user must satisfy himself that the product is entirely suitable for his purposes.