**Product Name: THERMOLASTIC CATALYST** 

Product Code: 935 CATALYST Date issued: 2/28/2018

#### **SECTION 1: IDENTIFICATION**

Product Name THERMOLASTIC CATALYST

Product Code # 935 CATALYST

Identified Uses Protective Coating

Manufacturer: Kelley Technical Coatings

1445 South 15<sup>th</sup> Street P.O. Box 3726

Louisville, Kentucky 40201-3726

Emergency Contact Number: Day: 502-636-2561 Night: 800-424-9300

Information Telephone Number: 502-636-2561

# **SECTION 2: HAZARDS IDENTIFICATION**

#### **GHS Classification**

Acute Toxicity - Oral 4 & 5

Skin Irritant 2 Skin Sensitization 1 Eye Damage/Irritation 2A Acute Toxicity - Inhalation 4

Specific Target Organ Toxicity (Repeated Exposure) 2

# **GHS Label Elements**

#### **Hazard Symbols**



# Signal Word Warning

#### **Hazard Statements**

H302 Harmful if swallowed

H315 Causes skin irritation

H317 May cause an allergic skin reaction

H319 Causes serious eye irritation

H332 Harmful if inhaled

H373 May cause damage to organs through prolonged or repeated exposure

#### Precautionary statements

### Prevention

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing dust/fume/gas/mist/vapor/spray.

P264 Wash hands and/or face thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

### Response

P330 If swallowed, rinse mouth.

P301 + P310 If swallowed: Immediately call a poison center or doctor.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

 $P333 + P313 \; If \; skin \; irritation \; or \; rash \; occurs: \; Get \; medical \; advice/attention.$ 

 $P337 + P313 \; If \; eye \; irritation \; persists: \; Get \; medical \; advice/attention.$ 

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

### Storage/ Disposal

 $P501\ Dispose\ of\ contents/container\ in\ accordance\ with\ federal,\ state,\ provincial,\ and\ local\ regulations.$ 

### Other Hazards OSHA Regulatory Status: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR1910.1200)

Product Name: THERMOLASTIC CATALYST

**Product Code: 935 CATALYST** Date issued: 2/28/2018

### SECTION 3: COMPOSITION INFORMATION

% by Weight Chemical Designation CAS No. manganese dioxide 1313-13-9 30 - 40% thiram 137-26-8 1 - 5%

#### **SECTION 4: FIRST AID MEASURES**

General Advice Show this safety data sheet to the doctor in attendance

Eyes: Flush with plenty of cool water for at least 15 minutes, holding eyelids apart for thorough irrigation. If irritation persists, get

immediate medical attention.

Skin: Wash affected area thoroughly with soap and water. If skin irritation persists, get immediate medical attention.

Inhalation: Move to fresh air. Restore breathing. If breathing is difficult, get immediate medical attention.

Ingestion: Do not induce vomiting – seek immediate medical attention.

Notes to Physician Treat symptomatically

### **SECTION 5: FIRE FIGHTING MEASURES**

Extinguishing Media: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Specific Hazards Closed containers may rupture if exposed to fire or extreme heat.

arising from the

Special protective

Chemical

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective

Equipment: gear.

#### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

Personal Precautions: Use personal protective equipment. Remove all sources of ignition.

Environmental Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from Precautions

entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages

cannot be contained.

Methods for Clean-up Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface

thoroughly.

Other Information None known

#### **SECTION 7: HANDLING & STORAGE**

Handling: Use only in area provided with appropriate exhaust ventilation. Do not breathe vapors or spray mist. Wear appropriate personal

protective equipment. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge,

all metal parts of the equipment must be grounded. Keep away from open flames, hot surfaces and sources of ignition.

Storage: Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat. Keep in properly labeled containers.

### SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

HMIS is a Health, Flammability and Reactivity rating: 2\*31

HMIS CODE: 4 - SEVERE HAZARD, 3 - SERIOUS HAZARD, 2 - MODERATE HAZARD, 1 - SLIGHT HAZARD, 0 - MINIMAL HAZARD, \* - Chronic Hazard Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual conditions of use.

**Exposure Limits** 

OSHA PEL ACGIH TLV **Hazardous Components** manganese dioxide 0.2 mg/m3 0.02 mg/m3 thiram 0.05 mg/m3 (I) 5 mg/m3

NE = None established NA = Not available (C) = Ceiling limit (I) = Inhalable fraction (IFV) = Inhalable fraction and vapor STEL = Short term exposure limit

(R) = Respirable fraction

**Engineering Measures** Ensure adequate ventilation, especially in confined areas.

### **Personal Protective**

**Product Name: THERMOLASTIC CATALYST** 

Product Code: 935 CATALYST Date issued: 2/28/2018

**Equipment** 

Eyes/Face: Safety goggles or full face shield
Skin: Protective gloves and impervious clothing.

Respiratory Protection: In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically

qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH

approved respirator specified for paint spray or organic vapors.

Hygiene Practices: Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after

handling. When using do not eat, drink or smoke.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES** 

Appearance: liquid
Odor: Solvent odor Odor threshold: Not determined

 VOC lb/gal
 0.00
 VOC (g/L)
 0.00

 VOC (lb/gal) less exempt
 0.00
 VOC (g/L) less exempt
 0.00

 Relative Density (LB/GAL):
 13.31
 Specific Gravity (g/L):
 1.60

Flash Point (F): 110

Flammability: Not determined Upper/lower flammability limits: Not available

Auto-ignition temperature: Not determined Decomposition temperature: Not determined

Evaporation rate : Not available

Vapor Pressure (mmHg): Not available Vapor Density: Not available Initial Boiling Point (F): Not available Boiling Point Range (F): Not available Freezing Point (F): Not determined Melting Point (F): Not determined Not available Viscosity Not available pН

Solubility (ies): Not determined
Partition coefficient: n- Not determined

octanol/water

#### **SECTION 10: STABILITY AND REACTIVITY**

Chemical Stability: Stable under normal conditions. Hazardous polymerization does not occur.

Conditions to Avoid: Keep away from open flames, hot surfaces, static electricity and sources of ignition.

Materials to Avoid: Incompatible with strong acids and bases and strong oxidizing agents.

Hazardous Decomposition Products: Thermal decomposition can lead to release of irritating gases and vapors.

Possibility of Hazardous Reactions: None under normal conditions of use.

# **SECTION 11: TOXICOLOGICAL INFORMATION**

**Acute Toxicity** 

Component LD50 Oral mg/kg (Rat) LD50 Dermal mg/kg (Rabbit) LC50 Inhalation mg/L (Rat, 4 hr.)

manganese dioxide NA NA NA NA thiram NA NA NA NA

**Chronic Toxicity** 

The information below indicates whether each agency has listed any ingredient as a carcinogen:

ComponentIARCNTPOSHANoneNoneNoneNone

# **SECTION 12: ECOLOGICAL INFORMATION**

No ecological information available

### **SECTION 13: DISPOSAL CONSIDERATION**

Waste Disposal Method Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your

sanitation department or state-designated environmental protection agency for more disposal options.

### **SECTION 14: TRANSPORT INFORMATION**

**Product Name: THERMOLASTIC CATALYST** 

Product Code: 935 CATALYST Date issued: 2/28/2018

Contact the manufacturer for shipping information.

#### **SECTION 15: REGULATORY INFORMATION**

US TSCA: Yes – All components are listed or exempt

# **Federal Regulations**

#### SARA 311/312 hazardous categorization

Acute Health Hazard YES
Chronic Health Hazard YES
Fire Hazard NO
Sudden Release of Pressure Hazard NO
Reactive Hazard NO

#### **SARA 313**

Section 313 OF Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). If listed below, this product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical Designation	Cas No.	Weight %
manganese dioxide	1313-13-9	30 - 40%
thiram	137-26-8	< 5%

### Clean Air Act, Section 112 Hazardous Air Pollutants (HAPS)

Chemical DesignationCas No.Weight %manganese dioxide1313-13-933.23

Any Target HAP listed in this section is not an OSHA Carcinogen unless listed as such in Section 11 under Chronic Toxicity.

### **State Regulations**

#### California Proposition 65

This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm.

# **SECTION 16: OTHER INFORMATION**

Date issued: 2/28/2018 VER Primary

The above Information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith. No warranty is implied with respect to the quality or the specification of the product and the user must satisfy himself that the product is entirely suitable for his purposes.