Product Name: VOC Compliant Solvent Product Code: X1111

SECTION 1: IDENTIFICATION

Product Name VOC Compliant Solvent
Product Code # X1111
Identified Uses Paint Thinner
Manufacturer: Kelley Technical Coatings
1445 South 15th Street
P.O. Box 3726
Louisville, Kentucky 40201-3726
Emergency Contact Number: Day: 502-636-2561
Night: 800-424-9300
Information Telephone Number: 502-636-2561

SECTION 2: HAZARDS IDENTIFICATION

GHS Classification

Flammable Liquid 3 Aspiration Hazard 1 Skin Irritant 2 Eye Damage/Irritation 2A Carcinogenicity 2 Specific Target Organ Toxicity (Single Exposure) 3

GHS Label Elements

Hazard Symbols



Signal Word Danger

Hazard Statements

H226 Flammable liquid and vapor

- H304 May be fatal if swallowed and enters airways
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H351 Suspected of causing cancer
- H336 May cause drowsiness or dizziness

Precautionary statements

Prevention

P202 Do not handle until all safety precautions have been read and understood.

- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating equipment.
- P271 Use only outdoors or in well-ventilated area.
- P280 Wear PPE to protect skin/eyes.
- P281 Use personal protective equipment as required.

Response

P312 Call a poison center or doctor if you feel unwell.

- P301 + P310 If swallowed: Immediately call a poison center or doctor.
- P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
- P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P308 + P313 IF exposed or concerned: Get medical advice/attention.
- P332 + P313 If skin irritation occurs: Get medical advice/attention.
- P337 + P313 If eye irritation persists: Get medical advice/attention.
- P303 + P361 + P353 IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

Storage/ Disposal

P405 Store locked up.

P501 Dispose of contents/container in accordance with federal, state, provincial, and local regulations.

Product Name: VOC Compliant Solvent Product Code: X1111

 $P403+P233 \ Store \ in \ well \ ventilated \ place. \ Keep \ container \ tightly \ closed. \\ P403+P235 \ Store \ in \ a \ well-ventilated \ place. \ Keep \ cool.$

Other Hazards OSHA Regulatory Status: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR1910.1200)

| SECTION 3: COMPOSITIO | N INFORMATION | |
|-----------------------------|---------------|-------------|
| Chemical Designation | CAS No. | % by Weight |
| VOC Exempt solvent | Trade Secret | >50% |
| light aromatic naphtha | 64742-95-6 | 1 - 5% |

SECTION 4: FIRST AID MEASURES

| General Advice | Show this safety data sheet to the doctor in attendance |
|--------------------|--|
| Eyes: | Flush with plenty of cool water for at least15 minutes, holding eyelids apart for thorough irrigation. If irritation persists, get |
| | immediate medical attention. |
| Skin: | Wash affected area thoroughly with soap and water. If skin irritation persists, get immediate medical attention. |
| Inhalation: | Move to fresh air. Restore breathing. If breathing is difficult, get immediate medical attention. |
| Ingestion: | Do not induce vomiting – seek immediate medical attention. |
| Notes to Physician | Treat symptomatically |
| | |

SECTION 5: FIRE FIGHTING MEASURES

| Extinguishing Media: | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
|----------------------|--|
| Specific Hazards | Closed containers may rupture if exposed to fire or extreme heat. |
| arising from the | |
| Chemical | |
| Special protective | As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective |
| Equipment: | gear. |

SECTION 6: ACCIDENTAL RELEASE MEASURES

| Personal Precautions: | Use personal protective equipment. Remove all sources of ignition. |
|-----------------------|---|
| Environmental | Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from |
| Precautions | entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages |
| | cannot be contained. |
| Methods for Clean-up | Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface |
| | thoroughly. |
| Other Information | None known |

SECTION 7: HANDLING & STORAGE

| Use only in area provided with appropriate exhaust ventilation. Do not breathe vapors or spray mist. Wear appropriate personal |
|---|
| protective equipment. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, |
| all metal parts of the equipment must be grounded. Keep away from open flames, hot surfaces and sources of ignition. |
| Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat. Keep in properly labeled containers. |
| |

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

HMIS is a Health, Flammability and Reactivity rating: 2*21

HMIS CODE: 4 - SEVERE HAZARD, 3 - SERIOUS HAZARD, 2 - MODERATE HAZARD, 1 - SLIGHT HAZARD, 0 - MINIMAL HAZARD, * - Chronic Hazard Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual conditions of use.

| Exposure Limits Hazardous Components | OSHA PEL | ACGIH TLV |
|---|----------|-----------|
| VOC Exempt solvent | 1000 ppm | 500 ppm |
| light aromatic naphtha | NE | NE |

NE = None established NA = Not available (C) = Ceiling limit (I) = Inhalable fraction (IFV) = Inhalable fraction and vapor STEL = Short term exposure limit (R) = Respirable fraction

SAFETY DATA SHEET

Product Name:VOC Compliant SolventProduct Code:X1111

| Engineering Measures | Ensure adequate ventilation, especially in confined areas. | | |
|----------------------------------|---|--|--|
| Personal Protective Equipment | | | |
| Eyes/Face: | Safety goggles or full face shield | | |
| Skin: | Protective gloves and impervious clothing. | | |
| Respiratory Protection: | In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator specified for paint spray or organic vapors. | | |
| Hygiene Practices: | Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling. When using do not eat, drink or smoke. | | |

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

| liquid | | |
|----------------|---|--|
| Solvent odor | Odor threshold: | Not determined |
| 0.20 | VOC (g/L) | 24.06 |
| 1.31 | VOC (g/L) less exempt | 156.92 |
| 6.76 | Specific Gravity (g/L): | 0.81 |
| 100.00 | | |
| Not determined | Upper/lower flammability limits: | Not available |
| Not determined | Decomposition temperature: | Not determined |
| Not available | | |
| Not available | Vapor Density : | Not available |
| Not available | Boiling Point Range (F): | Not available |
| Not determined | Melting Point (F): | Not determined |
| Not available | Viscosity | Not available |
| Not determined | | |
| Not determined | | |
| | | |
| | Solvent odor 0.20 1.31 6.76 100.00 Not determined Not determined Not available Not available Not available Not determined Not determined Not determined Not determined | Solvent odorOdor threshold:0.20VOC (g/L)1.31VOC (g/L) less exempt6.76Specific Gravity (g/L):100.00Upper/lower flammability limits:Not determinedDecomposition temperature:Not availableVapor Density :Not availableBoiling Point Range (F):Not determinedMelting Point (F):Not availableViscosityNot determinedViscosity |

SECTION 10: STABILITY AND REACTIVITY

| Chemical Stability: | Stable under normal conditions. Hazardous polymerization does not occur. |
|-------------------------------------|---|
| Conditions to Avoid: | Keep away from open flames, hot surfaces, static electricity and sources of ignition. |
| Materials to Avoid: | Incompatible with strong acids and bases and strong oxidizing agents. |
| Hazardous Decomposition Products: | Thermal decomposition can lead to release of irritating gases and vapors. |
| Possibility of Hazardous Reactions: | None under normal conditions of use. |
| | |

SECTION 11: TOXICOLOGICAL INFORMATION

| Component | LD50 Oral mg/kg (Rat) | LD50 Dermal mg/kg (Rabbit) | LC50 Inhalation mg/L (Rat, 4 hr.) |
|---------------------------|---|---|-----------------------------------|
| VOC Exempt solvent | NA | NA | NA |
| light aromatic naphtha | 8,400 | NA | NA |
| hronic Toxicity | antas whathar anah aganay has listad any in | gradient es a carainegan; | |
| he information below indi | cates whether each agency has listed any in | 6 6 | |
| | cates whether each agency has listed any in IARC None | gredient as a carcinogen: NTP None | OSHA None |

SECTION 12 : ECOLOGICAL INFORMATION

No ecological information available

SECTION 13 : DISPOSAL CONSIDERATION

Date issued: 2/28/2018

Product Name: VOC Compliant Solvent Product Code: X1111

Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

SECTION 14 : TRANSPORT INFORMATION

Contact the manufacturer for shipping information.

SECTION 15: REGULATORY INFORMATION

US TSCA:

Yes - All components are listed or exempt

<u>Federal Regulations</u> SARA 311/312 hazardous categorization

| 511/512 hazar dous categorization | | |
|-----------------------------------|-----|--|
| Acute Health Hazard | YES | |
| Chronic Health Hazard | YES | |
| Fire Hazard | YES | |
| Sudden Release of Pressure Hazard | NO | |
| Reactive Hazard | NO | |

SARA 313

Section 313 OF Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). If listed below, this product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

| Chemical Designation | Cas No. | Weight % |
|----------------------|---------|----------|
| None | None | None |

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPS)

| Chemical Designation | Cas No. | Weight % |
|----------------------|---------|----------|
| None | None | None |

Any Target HAP listed in this section is not an OSHA Carcinogen unless listed as such in Section 11 under Chronic Toxicity.

State Regulations

California Proposition 65

This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm.

SECTION 16: OTHER INFORMATION

Date issued: 2/28/2018 VER 01

The above Information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith. No warranty is implied with respect to the quality or the specification of the product and the user must satisfy himself that the product is entirely suitable for his purposes.