

# SAFETY DATA SHEET

**Product Name:** Skid Mix

**Product Code:** X905

**Date issued:** 4/18/2018

---

## SECTION 1 : IDENTIFICATION

Product Name Skid Mix

Product Code # X905

Identified Uses Protective Coating

Manufacturer: Kelley Technical Coatings  
1445 South 15<sup>th</sup> Street  
P.O. Box 3726  
Louisville, Kentucky 40201-3726

Emergency Contact Number: Day: 502-636-2561 Night: 800-424-9300

Information Telephone Number: 502-636-2561

---

## SECTION 2 : HAZARDS IDENTIFICATION

### GHS Classification

Eye Damage/Irritation 2A  
Carcinogenicity 1A and 1B  
Specific Target Organ Toxicity (Single Exposure) 3

### GHS Label Elements

#### Hazard Symbols



Signal Word Danger

#### Hazard Statements

H319 Causes serious eye irritation  
H350 May cause cancer  
H335 May cause respiratory irritation

#### Precautionary statements

##### Prevention

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P261 Avoid breathing dust/fume/gas/mist/vapor/spray.  
P264 Wash hands and/or face thoroughly after handling.  
P271 Use only outdoors or in well-ventilated area.  
P281 Use personal protective equipment as required.

##### Response

P312 Call a poison center or doctor if you feel unwell.  
P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P308 + P313 IF exposed or concerned: Get medical advice/attention.  
P337 + P313 If eye irritation persists: Get medical advice/attention.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

##### Storage/ Disposal

P405 Store locked up.  
P501 Dispose of contents/container in accordance with federal, state, provincial, and local regulations.  
P403 + P233 Store in well ventilated place. Keep container tightly closed.

### Other Hazards

**OSHA Regulatory Status:** This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Contains: Crystalline Silica which has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.

---

# SAFETY DATA SHEET

**Product Name: Skid Mix**

**Product Code: X905**

**Date issued: 4/18/2018**

---

## SECTION 3 : COMPOSITION INFORMATION

Chemical Designation	CAS No.	% by Weight
pumice	1332-09-8	>50%
crystalline silica, (quartz)	14808-60-7	1 - 5%

---

## SECTION 4 : FIRST AID MEASURES

General Advice	Show this safety data sheet to the doctor in attendance
Eyes:	Flush with plenty of cool water for at least 15 minutes, holding eyelids apart for thorough irrigation. If irritation persists, get immediate medical attention.
Skin:	Wash affected area thoroughly with soap and water. If skin irritation persists, get immediate medical attention.
Inhalation:	Move to fresh air. Restore breathing. If breathing is difficult, get immediate medical attention.
Ingestion:	Do not induce vomiting – seek immediate medical attention.
Notes to Physician	Treat symptomatically

---

## SECTION 5 : FIRE FIGHTING MEASURES

Extinguishing Media:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Specific Hazards arising from the Chemical	Closed containers may rupture if exposed to fire or extreme heat.
Special protective Equipment:	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

---

## SECTION 6 : ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Use personal protective equipment. Remove all sources of ignition.
Environmental Precautions	Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.
Methods for Clean-up	Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.
Other Information	None known

---

## SECTION 7 : HANDLING & STORAGE

Handling:	Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.
Storage:	Keep container tightly closed. Keep out of the reach of children.

---

## SECTION 8 : EXPOSURE CONTROLS / PERSONAL PROTECTION

HMIS is a Health, Flammability and Reactivity rating: **1\*00**

HMIS CODE: **4** – SEVERE HAZARD, **3** – SERIOUS HAZARD, **2** – MODERATE HAZARD, **1** – SLIGHT HAZARD, **0** – MINIMAL HAZARD,  
\* – Chronic Hazard

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual conditions of use.

### **Exposure Limits**

Hazardous Components	OSHA PEL	ACGIH TLV
pumice	15 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>
crystalline silica, (quartz)	10 mg/m <sup>3</sup> /%SiO <sub>2</sub> +2 (R)	0.025 mg/m <sup>3</sup> (R)

NE = None established NA = Not available (C) = Ceiling limit (I) = Inhalable fraction (IFV) = Inhalable fraction and vapor STEL = Short term exposure limit (R) = Respirable fraction

**Engineering Measures** Ensure adequate ventilation, especially in confined areas.

### **Personal Protective Equipment**

<b>Eyes/Face:</b>	Safety goggles or full face shield
<b>Skin:</b>	Protective gloves and impervious clothing.
<b>Respiratory Protection:</b>	In case of insufficient ventilation, wear suitable respiratory equipment.

**Hygiene Practices:** Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

---

# SAFETY DATA SHEET

**Product Name: Skid Mix**

**Product Code: X905**

**Date issued: 4/18/2018**

---

## **SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**

Appearance:	White granular powder		
Odor:	Little or no odor	Odor threshold:	Not determined
VOC (lb/gal)	0.00	VOC (g/L)	0.00
VOC (lb/gal) less exempt	0.00	VOC (g/L) less exempt	0.00
Relative Density (LB/GAL):	17.99	Specific Gravity (g/L):	2.16
Flash Point (F):	Not available		
Flammability:	Not applicable	Upper/lower flammability limits:	Not applicable
Auto-ignition temperature:	Not applicable	Decomposition temperature:	Not determined
Evaporation rate :	Not available		
Vapor Pressure (mmHg) :	Not available	Vapor Density :	Not available
Initial Boiling Point (F):	Not available	Boiling Point Range (F):	Not available
Freezing Point (F):	Not available	Melting Point (F):	Not determined
pH	Not available	Viscosity	Not available
Solubility (ies):	Not determined		
Partition coefficient: n-octanol/water	Not determined		

---

## **SECTION 10 : STABILITY AND REACTIVITY**

Chemical Stability: Stable under normal conditions.  
Conditions to Avoid: Avoid formation of dust.  
Materials to Avoid: No materials to be especially mentioned.  
Hazardous Decomposition Products: None under normal use.  
Possibility of Hazardous Reactions: None under normal conditions of use.

---

## **SECTION 11 : TOXICOLOGICAL INFORMATION**

### **Acute Toxicity**

Component	LD50 Oral mg/kg (Rat)	LD50 Dermal mg/kg (Rabbit)	LC50 Inhalation mg/L (Rat, 4 hr.)
pumice	NA	NA	NA
crystalline silica, (quartz)	500	NA	NA

### **Chronic Toxicity**

The information below indicates whether each agency has listed any ingredient as a carcinogen:

Component	IARC	NTP	OSHA
crystalline silica, (quartz)	1 – Human carcinogen	Known Human Carcinogen	Listed

---

## **SECTION 12 : ECOLOGICAL INFORMATION**

No ecological information available

---

## **SECTION 13 : DISPOSAL CONSIDERATION**

Waste Disposal Method: Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

---

## **SECTION 14 : TRANSPORT INFORMATION**

Contact the manufacturer for shipping information.

---

## **SECTION 15 : REGULATORY INFORMATION**

US TSCA: Yes – All components are listed or exempt

### **Federal Regulations**

**SARA 311/312 hazardous categorization**

Acute Health Hazard YES

# SAFETY DATA SHEET

**Product Name: Skid Mix**

**Product Code: X905**

**Date issued: 4/18/2018**

---

Chronic Health Hazard	YES
Fire Hazard	NO
Sudden Release of Pressure Hazard	NO
Reactive Hazard	NO

### SARA 313

Section 313 OF Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). If listed below, this product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical Designation	Cas No.	Weight %
None	None	None

### Clean Air Act, Section 112 Hazardous Air Pollutants (HAPS)

Chemical Designation	Cas No.	Weight %
None	None	None

Any Target HAP listed in this section is not an OSHA Carcinogen unless listed as such in Section 11 under Chronic Toxicity.

### State Regulations

#### California Proposition 65

This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm.

---

### SECTION 16 : OTHER INFORMATION

Date issued: 4/18/2018      VER 01

The above Information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith. No warranty is implied with respect to the quality or the specification of the product and the user must satisfy himself that the product is entirely suitable for his purposes.